

JZDRA-92: Drying Rack


CONSTRUCTION/MATERIAL:

- Sturdy construction specifically designed for the demanding corrections environment
- All welded construction
- All fasteners are tamper-proof

JZDRA (Aluminum)

- Type 6063-T5 aluminum alloy with wall thickness of 0.070"

WARRANTY:

- Aluminum: 5-year warranty against manufacturing defect

DIMENSIONS:

Height: 72.63" Width: 80.50" Depth: 22.88"

CAPACITY:

<i>Insulated Trays</i>		<i>Segregation Trays</i>	
PRTS-5000 (15" x 11" x 2")	184	Large	184
PRTS-4000 or 4001 (15" x 13" x 2.5")	184	Medium & Small	276
PRTS-6000 (15" x 14" x 2.875")	184	<i>Self-Stacking Trays</i>	
		SmartTray	184

* with 2" overhang

COMPONENTS:
Shelves


- Four shelves
- Eight inserts per shelf, thirty-two inserts per rack
- Interchangeable inserts – mix and match

Casters

- Four 6" poly swivel casters with brakes

INSERTS

- Inserts made of copolymer material:
 - Dishwasher safe, temps up to 212°
 - Shatterproof and resists sharpening


JZDRI-3

- Large, fewer slots 3" spacing
- 23 slots per shelf, 92 per rack
- Run inserts through dishwasher for better sanitation and restore to "like new"
- Plastic inserts prolong life of plastic trays instead of scraping over all metal drying racks