

JZHA-168XL: Heated/Ambient Cart (with removable heater)



DIMENSIONS:		
Height: 47.50"	Width: 62.90"	Depth: 32.50"

CAPACITY:			
Segregation Trays		Bulk Food	
9000 series	168	18x26 sheet pans	14
5000 series	252	12x20 hotel pans	28
4000 series	320		
		Non-Insul Stacking	
		JZ SmartTray	n/a
		JZ SmartTray XD	n/a
		Rock	n/a
		X-tray	n/a

CONSTRUCTION/MATERIAL:
<ul style="list-style-type: none"> • 18-gauge 304 series stainless steel exterior and 20-gauge interior • Base frame made of 16-gauge stainless steel with reinforced cross channels • All fasteners are security type • All welds are ground and polished

HEATING/ELECTRICAL
<ul style="list-style-type: none"> • Side-mount 1000w snap-in removable heating assembly left side • 120 volts 1700 watts 14.2 Amps • NEMA plug: 5-15P • Stainless steel strain relief on electrical cord • 12-gauge cord wrap on heat box • Right side ambient / non-heated with insulated center wall

WARRANTY AND UPTIME KIT:
<ul style="list-style-type: none"> • 1-year parts and labor warranty • Uptime kit available

COMPONENTS:
<p>Doors</p> <ul style="list-style-type: none"> • Magnetic closure double door, door gasket • Three heavy-duty 12-gauge stainless steel hinges • Drop down padlocking door latch <p>Display</p> <ul style="list-style-type: none"> • Solar-powered digital thermometer <p>Insulation</p> <ul style="list-style-type: none"> • Fully insulated in top, bottom, and sides with 1" thick high-density fiberglass <p>Racks</p> <ul style="list-style-type: none"> • Removable universal racks for steam pans or sheet pans (optional) <p>Handles</p> <ul style="list-style-type: none"> • Push/pull handle on each side • Three-sided tubular top rail <p>Casters</p> <ul style="list-style-type: none"> • Six 6" casters mounted to 1/4" plates • Premium multi-terrain (4 swivel with brake, 2 rigid) • Turns on its own axis on center casters <p>Bumper</p> <ul style="list-style-type: none"> • Full perimeter non-marking vinyl bottom bumper <p>Heavy Duty Corrections Package</p> <ul style="list-style-type: none"> • Welded hinges, welded corners • Lag bolts to retain nylon bumper from pulling out